



Inlay Layout and Dimensions

	IN410
Antenna width	50 mm ± 0.2 mm (1.97 ± 0.01 in)
Antenna length	50 mm ± 0.2 mm (1.97 ± 0.01 in)
Lengthwise pitch	60 mm ± 0.2 mm (2.36 ± 0.01 in)
Web width	60 mm ± 0.2 mm (2.36 ± 0.01 in)

Inlay Composition

Composition	Material	Thickness* [µm]
Top	Aluminium	30
Support	Polyester PET	38
Bottom	Aluminium	10 ÷ 20

* Overall thickness depends on the IC. For IC thickness please refer to the "Available ICs" table

Available ICs

	NXP ICODE SL2 ICS20	NXP ICODE SLI-S ICS53	NXP ICODE SLI-L ICS50	TI HF-I STD/PRO	ST LRI2K
Product code	IN410-PSL2	IN410-PSSS	IN410-PSLL	IN410-TISD	IN410-LR2K
Operating frequency	13.56 MHz	13.56 MHz	13.56 MHz	13.56 MHz	13.56 MHz
Standard compliance	ISO 15693 ISO 18000-3	ISO 15693 ISO 18000-3	ISO 15693 ISO 18000-3	ISO 15693 ISO 18000-3	ISO 15693 ISO 18000-3
Thickness	150µm ± 15µm	150µm ± 15µm	150µm ± 15µm	150µm ± 15µm	180µm ± 15µm
Operating temperature	-25°C to +85°C	-25°C to +85°C	-25°C to +85°C	-25°C to +70°C	-20°C to +85°C
Storage temperature	-55°C to +140°C	-55°C to +140°C	-55°C to +140°C	-40°C to +85°C	na
Unique serial number	8 bytes	8 bytes	8 bytes	8 bytes	8 bytes
Memory size	1024 bits	2048 bits	512 bits	256 bits	2048 bits
Memory organization	32 blocks of 4 bytes	16 pages with 4 blocks of 4 bytes	16 blocks of 4 bytes	8 blocks of 4 bytes	64 blocks of 4 bytes
Write endurance	10 years	10 years	10 years	10 years	40 years
Data retention	100 000 cycles	100 000 cycles	100 000 cycles	100 000 cycles	1 000 000 cycles

General supply conditions

Reel dimensions	Internal diameter	76 mm
	External diameter	300 mm
Reel quantity	Inlay per reel	8000 ± 10% (custom sizes available upon request)