



Inlay Layout and Dimensions

	IN580
Antenna width	16 mm ± 0.2 mm (0.63 ± 0.01 in)
Antenna length	30 mm ± 0.2 mm (1.18 ± 0.01 in)
Lengthwise pitch	40 mm ± 0.2 mm (1.57 ± 0.01 in)
Web width	24 mm ± 0.2 mm (0.94 ± 0.01 in)

Inlay Composition

Composition	Material	Thickness* [µm]
Top	Aluminium	30
Support	Polyester PET	38
Bottom	Aluminium	10 ÷ 20
Adhesive	PSA	25
Protective layer	Polyester PET	12

* Overall thickness depends on the IC. For IC thickness please refer to the "Available ICs" table

Available ICs

ISO15693 ICs	NXP ICODE SL2 ICS20	NXP ICODE SLI-S ICS53	NXP ICODE SLI-L ICS50	EM 4233	ST LRI2K
Product code	IN580-PSL2	IN580-PSSS	IN580-PSLL	IN580-EM4233	IN580-LR2K
Operating frequency	13.56 MHz	13.56 MHz	13.56 MHz	13.56 MHz	13.56 MHz
Standard compliance	ISO 15693 ISO 18000-3	ISO 15693 ISO 18000-3	ISO 15693 ISO 18000-3	ISO 15693 ISO 18000-3	ISO 15693 ISO 18000-3
Thickness	150µm ± 15µm	150µm ± 15µm	150µm ± 15µm	280µm ± 15µm	180µm ± 15µm
Operating temperature	-25°C to +85°C	-25°C to +85°C	-25°C to +85°C	-40°C to +85°C	-20°C to +85°C
Storage temperature	-55°C to +140°C	-55°C to +140°C	-55°C to +140°C	-55°C to +125°C	n/a
Unique serial number	8 bytes	8 bytes	8 bytes	8 bytes	8 bytes
Memory size	1024 bits	2048 bits	512 bits	2048 bits	2048 bits
Memory organization	32 blocks of 4 bytes	16 pages with 4 blocks of 4 bytes	16 blocks of 4 bytes	52 blocks of 4 bytes	64 blocks of 4 bytes
Write endurance	10 years	10 years	10 years	60 years	40 years
Data retention	100 000 cycles	100 000 cycles	100 000 cycles	100 000 cycles	1 000 000 cycles

Other ICs are available upon request (Tag-it Std/Pro family)

ISO14443 ICs	NXP Mifare Ultralight	NXP Mifare Ultralight C	NXP Mifare Mini	NXP Mifare Std 1k	NXP Mifare Std 4k
Product code	IN580-PMF2	IN580-PMFUC	IN580-PMFM	IN580-PM1K	IN580-PM4K
Operating frequency	13.56 MHz	13.56 MHz	13.56 MHz	13.56 MHz	13.56 MHz
Standard compliance	ISO 14443 A (up to level 3)	ISO 14443 A (up to level 3)	ISO 14443 A (up to level 3)	ISO 14443 A (up to level 3)	ISO 14443 A (up to level 3)
Thickness	120µm ± 15µm	120µm ± 15µm	150µm ± 15µm	150µm ± 15µm	150µm ± 15µm
Operating temperature	-25°C to +70°C	-25°C to +70°C	-25°C to +70°C	-25°C to +70°C	-25°C to +70°C
Storage temperature	-55°C to +125°C	-55°C to +125°C	-55°C to +125°C	-55°C to +125°C	-55°C to +125°C
Unique serial number	7 bytes	7 bytes	4 bytes	4 bytes	4 bytes
Memory size	64 bytes	192 bytes	320 bytes	1024 bytes	4096 bytes
Memory organization	16 pages of 4 bytes	48 pages of 4 bytes	5 sectors of 64 bytes	16 sectors of 64 bytes	32 sectors of 64 bytes + 8 sectors of 256 bytes
Write endurance	5 years	5 years	10 years	10 years	10 years
Data retention	10 000 cycles	10 000 cycles	100 000 cycles	100 000 cycles	100 000 cycles

Other ICs are available for this antenna (Mifare Plus, DESFire and Infineon families): please contact us for further information

General supply conditions

Reel dimensions	Internal diameter	76 mm
	External diameter	300 mm
Reel quantity	Inlay per reel	10 000 ± 10% (custom sizes available upon request)